Bolt fixing of multiple joists

(Withdrawn - January 2024)

The Technical Guidance Notes are produced by NHBC as guidance solely for our builder customers as to how to interpret the technical requirements in relation to the warranty cover provided by NHBC under its Buildmark, Buildmark Choice, Buildmark Link, Buildmark Solo, Buildmark Connect or any similar product from time to time. It has not been created or intended for distribution or use outside of that purpose. The information contained in this Technical Guidance Note does not constitute advice and is not to be relied upon by any third party. Nothing in this Technical Guidance Note is intended to, nor should it be taken to, create any legal or contractual relationship. Any third party who chooses to rely upon the information contained in the Technical Guidance Notes shall do so entirely at their own risk and NHBC accepts no duty of care or liability, however caused, in connection with its use or reliance by any third party.

Question

Can coach bolts be used to fix multiple joists together and, if so, which methods of installation are acceptable?

Considerations

NHBC Standards clause 6.4-S7 refers to the use of bolts for fixing multiple joists together.

Answer

Coach bolts can be used to fix multiple joists together. They should be on the centre line at approximately Im centres. A washer should be fitted under the nut of the bolt. If the design requires a washer under the head of the bolt, the square shank on the bolt should pass through the washer. Metal toothed/ring connectors may also be required, depending on the design.



NHBC, NHBC House, Davy Avenue, Knowlhill, Milton Keynes, Bucks MK5 8FP Tel: 0344 633 1000 Web: nhbc.co.uk